

High Grade EPDM Rubber Sheet – Peroxide Cured

Product Code: RC0302-PC

Product Description

A peroxide cured high grade EPDM rubber produces very stable carbon to carbon bonds, which results in superior material stability. This creates a material that performs better at higher temperatures as well as providing superior resistance to heat ageing and compression set.



Available In -



Full Rolls



Cut to strip



Bespoke Gaskets

Technical Specification

Properties	Test Method	Values
Product		High Grade EPDM Rubber Sheeting
Compound		EPDM
Hardness (Shore A)		70° ± 5°
Density		1.22 g/cm ²
Tensile Strength		9 N/mm ²
Elongation at Break		200%
Compression Set (22h, 100°C)	DIN ISO 815	25%
Working Temperature Range		-40°C to + 120°C



ISO
9001 : 2015
REGISTERED

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

Standard Sizes

Properties
0.5mm x 1.4m x 20m
1mm x 1.4m x 20m
1.5mm x 1.4m x 20m
2mm x 1.4m x 20m
3mm x 1.4m x 10m
4mm x 1.4m x 10m
5mm x 1.4m x 10m
6mm x 1.4m x 10m
8mm x 1.4m x 5m
10mm x 1.4m x 5m
12mm x 1.4m x 5m
15mm x 1.4m x 5m
20mm x 1.4m x 5m
25mm x 1.4m x 5m
30mm x 1.4m x 5m
40mm x 1.4m x 5m



ISO
9001 : 2015
REGISTERED

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.