

# 南京宇航橡胶有阻公司 NANJING YUHANG RUBBER CO.LTD

Manufacturers · Designers · Distributors

### Commerical Grade EPDM Rubber Sheet Datasheet

Product Code: RC0348

#### **Product Description**

Our commercial grade EPDM rubber provides a cost effective solution to customers who require a versatile, general purpose material. This product is the ideal solution for use in simple, everyday applications. Popular uses for this product includes; packing pieces, dust seals, protection pads and many more.



#### **Technical Specification**

Properties	Values
Product	Commercial grade sheeting
Compound	EPDM 25% / SBR
Hardness (Shore A)	65° ± 5°
Density (Specific Gravity)	1.35 g/cm <sup>2</sup>
Tensile Strength	60 kg/cm²
Elongation at Break	300%
Compression Set (24hrs @ 70°C)	35%
Working Temperature Range	-30°C to + 100°C





The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.



# 南京宇航橡胶有阻公司 NANJING YUHANG RUBBER CO.LTD

Manufacturers · Designers · Distributors

#### **Standard Sizes**

Properties	Tolerances
1mm x 1.4m x 10m	+/- 0.2mm
1.5mm x 1.4m x 10m	+/- 0.3mm
3mm x 1.4m x 10m	+/- 0.3mm
4mm x 1.4m x 10m	+/- 0.4mm
5mm x 1.4m x 10m	+/- 0.4mm
6mm x 1.4m x 10m	+/- 0.5mm

### Made To Order Sizes - Subject To Minimum Order Quantities

Properties	Tolerances
0.5mm x 1.4m x 10m	+/- 0.2mm
8mm x 1.4m x 5m	+/- 0.7mm
10mm x 1.4m x 5m	+/- 1mm
15mm x 1.4m x 5m	+/- 1mm
20mm x 1.4m x 5m	+/- 1.4mm
25mm x 1.4m x 5m	+/- 1.75mm
32mm x 1m x 1m	-
38mm x 1m x 1m	-
40mm x 1m x 1m	-





The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.