

Anti Static Neoprene Sheeting BS490 & ISO340

Product Code: RC0330

Product Description

Our anti static neoprene sheeting is a high grade material that fully confirms to BS490 and ISO340 specifications for flame retardant applications. The combination of anti-static and flame retardant properties ensure that our product is suitable for a wide range of transportation as well as manufacturing industries.

Technical Specification



Available In -



Full Rolls



Cut to strip



Bespoke
Gaskets

| Properties | Values |
|---|--|
| Product | Anti-Static & Flame Retardant Sheeting |
| Compound | CR/SBR |
| Hardness (Shore A) | 60° ± 5° |
| Density | 1.20 g/cm ² |
| Tensile Strength | 80 Kg/cm ² |
| Elongation at Break | 250% |
| Compression Set (22h, 70°C) | 25% |
| Working Temperature Range | -30°C to + 100°C |
| Flame Resistance (according to ISO 340) | |
| Flame persistence (After Removing the Burner) | Max 45s |
| Anti-static Characteristic (according to BS 490) | |
| Surface Electrical Resistance | 3 x 10 ⁸ Ω (Max) |



ISO
9001 : 2015
REGISTERED

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

Standard Sizes

| Properties | Weight [kg/m ²] |
|----------------------|-----------------------------|
| 1.5mm x 1400mm x 20m | 2.25 |
| 3mm x 1400mm x 10m | 4.50 |
| 6mm x 1400mm x 10m | 9.00 |
| 10mm x 1400mm x 10m | 15.00 |

Made To Order Sizes

| Properties | Weight [kg/m ²] |
|--------------------|-----------------------------|
| 1mm x 1400mm x 20m | 1.50 |
| 2mm x 1400mm x 10m | 3.00 |
| 4mm x 1400mm x 10m | 6.00 |
| 5mm x 1400mm x 10m | 7.50 |
| 12mm x 1400mm x 5m | 18.00 |



ISO
9001 : 2015
REGISTERED

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.