

# 南京宇航橡胶有阻公司 NANJING YUHANG RUBBER CO.LTD

Manufacturers · Designers · Distributors

### Transparent PVC-P Irrigation Hose Datasheet

Product Code: RC07-I-111

#### **Product Description**

Transparent PVC-P hose reinforced with high tenacity polyester yarn.

### **Technical Specification**

Ø INT.	Ø OUT.	Weight	W.P.	B.P.	Bending	Coil Length	Volume
mm	mm	g/m	bar	bar	mm	m	m³
6	11	85	21	63	30	100	0.023
6	12	105	21	63	30	100	0.025
8	13	105	23	69	40	100	0.028
8	14	130	23	69	40	100	0.032
9	15	140	18	54	50	100	0.036
10	15	120	16	48	50	100	0.036
10	16	150	16	48	50	100	0.041
12	17	140	12	36	60	100	0.044
12	18	175	12	36	60	100	0.050
12.5	18.5	180	11	36	60	100	0.051
13	19	185	11	33	70	100 (JP 50/100)	0.058
15	20	170	11	33	80	50	0.034
15	21	210	10	33	80	50	0.035
15	23	295	10	30	80	50	0.042
16	21	180	10	30	80	50	0.035
16	22	220	9	30	80	50	0.041
19	25	255	9	27	100	50	0.083
19	26	305	8	27	100	50	0.085
25	32	385	8	24	130	50	0.099

The technical data here reported has been measured at 23°C with 50% humidity.

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.



# 南京宇航橡胶有阻公司 NANJING YUHANG RUBBER CO.LTD

Manufacturers · Designers · Distributors

#### **Technical Specification**

Ø INT.	ø о <b>ит</b> .	Weight	W.P.	B.P.	Bending	Coil Length	Volume
mm	mm	g/m	bar	bar	mm	m	m³
25	33	450	8	24	130	50	0.102
30	38	525	6	18	150	50	0.141
32	42	710	5	15	160	50	0.168
38	48	825	4	12	190	50	0.271
40	50	865	4	12	200	50	0.303
50	62	1290	4	12	250	50	0.391

The technical data here reported has been measured at 23°C with 50% humidity.

The sizes highlighted in green are from our stock in Italy - subject to 2/3 weeks lead time.

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.