

南京宇航橡胶有阻公司 NANJING YUHANG RUBBER CO.LTD

Manufacturers · Designers · Distributors

Grey TPU Flame Resistant Ducting 180°C Datasheet

Product Code: RC07-I-119

Product Description

Grey duct made with flame resistant TPU coated polyester fabric and reinforced by steel spiral welded between the two layers.

Technical Specification

Ø INT.	Weight	Bending	Coil Length	Volume
mm	g/m	mm	m	m³
40	125	20	10	0.002
45	140	23	10	0.002
51	150	26	10	0.003
55	165	28	10	0.003
60	175	30	10	0.004
63	185	32	10	0.004
65	190	33	10	0.005
70	185	35	10	0.005
76	200	38	10	0.006
80	210	40	10	0.007
82	215	41	10	0.007
90	240	45	10	0.009
102	310	51	10	0.011
107	325	54	10	0.012
110	330	55	10	0.013
115	345	58	10	0.014
120	360	60	10	0.015
127	385	64	10	0.017
130	390	65	10	0.018
140	420	70	10	0.021
152	460	76	10	0.024
160	470	80	10	0.027
163	475	82	10	0.028

The technical data here reported has been measured at 23 °C with 50% humidity.

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

南京宇航橡胶有阻公司 NANJING YUHANG RUBBER CO.LTD

Manufacturers · Designers · Distributors

Technical Specification

Ø INT.	Weight	Bending	Coil Length	Volume
mm	g/m	mm	m	m³
180	525	90	10	0.034
203	595	102	10	0.043
220	640	110	10	0.050
228	665	114	10	0.054
254	910	127	10	0.067
279	1000	140	10	0.080
305	1095	153	10	0.124
315	1130	158	10	0.102
330	1180	165	10	0.112
356	1275	178	10	0.130
406	1455	203	10	0.236
500	2015	250	10	0.357
505	2035	253	10	0.364

The technical data here reported has been measured at 23 °C with 50% humidity.

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.